



## Medical Tablet 313T/MD

Slim, Anti-microbial, ANSI/AAMI ES60601-1 Certified Tablet for Efficient Operations

The 313T/MD Medical Tablet features the integration of a brilliant 13.3" capacitive touch screen and a high performance, energy-efficient Intel® Core™ i series processor within a slim, durable package. With built-in Wi-Fi and Bluetooth as well as options for data capture modules, this robust tablet offers health professionals an effective tool to monitor, record and retrieve patient information. With its large, vivid display, the 313T/MD Medical Tablet shows a wide work area and detailed application interface to enhance user experience and workflow.

### Features:

- 13.3" full-HD LCD display with capacitive touch, digital pen support
- Intel® 11th Generation Core™ i5 processor
- NIST compliant BIOS available
- Built-in front and back cameras
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- High capacity, hot-swappable battery pack
- Built-in foldable tabletop stand and optional handle

<b>System</b>		<b>313T/MD</b>
CPU	Intel® Core™ i5-1135G7, 4-Core, up to 4.2GHz, Intel® Core™ i7-1165G7, 4-Core, up to 4.7GHz	
RAM	8GB to 32GB	
Storage	256GB to 2TB Flash	
Operating System	Microsoft® Windows® 10/11 IoT Enterprise	
NIST Compliance	NIST compliant BIOS available	
Display	13.3" LED-backlit Touchscreen, outdoor viewable	
Display Resolution	1920 x 1080	
Camera	Full-HD front camera and 8 megapixel back camera	
Buttons	1 power button, 1 trigger button, 3 programmable buttons	
Microphone & Speaker	Built-in Microphone & Speaker	
<b>Network Interface</b>		
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band	
<b>I/O Ports</b>		
USB Port	USB 3.0 x 1, USB 2.0 x 2	
Headset Jack	1(3.5mm)	
Ethernet Port	1(RJ45)	
HDMI-out	1	
DC-in	1	
<b>Mechanical Environment</b>		
Battery Pack	Hot swappable battery, 5400mAh	
AC/DC Adapter	Input: 100 - 240V AC; Output: 19V DC, 3.42A	
Enclosure	ABS + PC plastics and magnesium-aluminum alloy; anti-microbial enclosure	
Dimensions (HxWxD)	256 x 335 x 21 mm	
Weight	1.8 kg	
Durability	N/A	
Regulatory	FCC/IC, CE/CB, RCM, CCC, ANSI/AAMI ES60601-1	
Temperature	Operation: 0°C - 40°C; Storage: -55°C - 70°C	
Humidity	0% - 90% non-condensing	
<b>Major Options</b>		
Barcode Scanner	2D scanner, reads 1D & 2D	