



17" Medical Grade All-In-One Computer/Tablet 373T/MD

Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablet for Efficient Operations

The 373T/MD All-In-One computer/tablet features the integration of a brilliant 17" capacitive touch screen and a high performance, energy-efficient Intel® Core™ i processor within a slim, durable package. With built-in front and back cameras, Wi-Fi as well as optional data capture modules, this medical AIO computer/tablet offers health professionals an effective tool to monitor, record and retrieve patient information. With its large, vivid display, the 373T/MD shows a wide work area and detailed application interface to enhance user experience and workflow.

Features

- 17" Full-HD capacitive touch screen, digital pen support
- Intel® 13th Generation Core™ i5 processor
- NIST compliant BIOS available
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- IP65-rated front panel
- Hot-Swappable battery pack
- Built-in front and back cameras
- VESA plate compatible for mounting

Major Options

- CAC card reader

System		373T/MD
CPU	Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz	
RAM	8GB to 16GB	
Storage	256GB to 1TB Flash	
Operating System	Microsoft® Windows® 10/11 IoT Enterprise	
NIST Compliance	NIST Compliant BIOS Available	
Display	17" LED-Backlit Touchscreen	
Display Resolution	1920 x 1080	
WLAN	Wi-Fi 802.11ax, 2.4GHz/ 5GHz dual band	
Control Switch and Buttons	1 x Power Button, 3 x Programmable Buttons	
Microphone & Speaker	Built-In Microphone and Speaker	
Camera	Full-HD Front Camera & 8 MP Back Camera	
I/O Ports		
USB Port	6 x USB 3.0, 1 x USB Type C	
Headset Jack	1 (3.5 mm)	
Ethernet Port	1 (RJ45)	
DC-in	1	
Mechanical and Environmental		
AC/DC Adapter	Input: 100-240V AC; Output: 18.5V DC, 3.89A	
Battery Pack	Hot-Swappable Battery (11.4V, 5400mAh)	
Enclosure	ABS + PC Plastics and Magnesium-Aluminum Alloy with Antimicrobial Enclosure	
Dimensions (H x W x D)	430 X 282 X 27mm	
Weight	2 kg	
VESA-compliant Mounting	75mm x 75mm VESA standard	
Durability	IP65-Rated Front Panel	
Regulatory	FCC/IC, CE/CB, RCM, ANSI/AAMI ES60601-1	
Temperature	Operation: 0°C to 40°C, Storage: -55°C to 70°C	
Humidity	0% - 90% non-condensing	
Major Options Specs		
CAC reader	Full-Slot (Reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card	