

# PURA

Optimal Positioning for Superior  
Patient & Staff Comfort



Dialysis, Oncology, and Treatment Chair Solution

# TRANSPORT

Patient transport is safe and requires minimal physical effort:

- Patients can be safely transported directly on the treatment chair within hospital departments.
- Fold-away handles enable rapid and unobstructed transfer of patients from the treatment chair to stretcher/trolley in emergency situations.



## 5th castor

A 5th castor on the undercarriage is an optional feature. This ingenious mechanism allows you to better manoeuvre the chair in confined spaces, corridors, or in lifts.



LINET | Pura

# SAFE AND COMFORTABLE CARE

Patient and staff comfort is ensured by an ergonomical frame and soft padding.

- The height-adjustable seating system supports maximum staff comfort when attending to patients.
- Multi-position adjustable arm rests with gutter padding ensure maximum patient comfort during treatment, and effective access/positioning for healthcare staff to initiate treatment.
- Base design enables easy introduction of mobile patient lifting equipment.



## Entering and exiting the chair

Height adjustment for patient safety and enhanced staff ergonomics.

# VARIABILITY IN POSITIONING

The versatile range of adjustable positions makes the Pura chair adaptable for a wide variety of applications, ensuring optimal functionality.

- Upright sitting, zero-gravity recline, full recline, and horizontal positions – including full Trendelenburg positioning.
- Low chair height provides a safe patient ingress/egress to/from the sitting position.

## Horizontal position

Horizontal position supports emergency treatment, comfort, and patient transport.



## Portable hand control

Full function hand control features both electric and manual CPR release function.

LINET | Pura

# TECHNICAL SPECIFICATIONS

Length	Total rest area	2,123 mm
Width	Seat section	590 mm
Height (castors 100 mm)	MAX. – rest area to seat section	934 mm
Height (castors 150 mm)	MAX. – rest area to seat section	970 mm
Castors	Castor diameter / brake	100 mm / individually braked
	Castor diameter / brake	150 mm / central brake
Adjustment angles	Back section	70°
	Armrest – vertical	+ 42° / – 8.5°
	Armrest – horizontal	360°
Electrical parameters	Protection against water and dust	IPX4
	Device protection class	I.
	Classification of applied parts	B
	Batteries back up voltage	24 V / 1.2 Ah
	Voltage – input	100–240 V
Trendelenburg position (TR)		12°
Safe Working load		255 kg
Maximum patient weight		190 kg

## COLOUR OPTIONS

Standard colours



Blue



Yellow



Orange



Green



Lavender

Non-standard colours




**wissner-**  
**bossenhoff**

**LINET**

Members of LINET Group

LINET spol. s r.o. | Želevčice 5, 274 01 Slaný | Czech Republic  
 tel.: +420 312 576 400 | fax: +420 312 522 668 | e-mail: info@linet.com | www.linet.com

